



Equipment:

- Lower arm (except longitudinal type)
- Electronic flowmeter

Options:

- Increase to 220 V
- Wheel trimmer
- Double drive and differential
- Double peripheral drive

Gamma 100

Gamma 200

		Transversal			Longitudinal			Mixed			Transversal			Longitudinal			Mixed	
	Ref	73101	73102	73103	73104	73105	73111	73106	73107	73108	73109	73110	73113	73114	73115	73117	73118	
Power at 50 % DC	kVA				130								250					
Cylinder force at 6 bar	daN				750								1200					
Cylinder stroke	mm				100								150					
DIN throat depth (head axe)	mm	600	750	1050	600	750	1050	600	750	600	750	1050	600	750	1050	710	860	
Daylight	mm	710	860	1160	600	750	1050	710	860	710	860	1160	600	750	1050	710	860	
Max. welding power in Sh.C.	kA	24	19.2	16	24	19.2	16	24	24	24	30	24	24	24	27	24	27	
Max. tangential speed	m/min	3.4	4.5	4.5	4.5	4.5	4.5	4.5	4.5	5	6	6	6	6	6	6	6	
Min. tangential speed	m/min	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	
Height	mm	2060	2060	2060	2060	2060	2060	2060	2060	2060	2060	2060	2060	2060	2060	2060	2060	
Length	mm	1610	1760	2060	1610	1760	1660	1610	1760	1610	1760	2060	1610	1760	2060	1610	2060	
Width	mm	722	722	722	722	722	722	722	722	722	722	722	722	722	722	722	722	
Wheel Diameter	mm	170	170	170	170	170	170	170	170	250	250	250	250	250	250	250	250	
Weight	kg	1200	1250	1300	1200	1200	1250	1200	1300	1290	1340	1390	1330	1360	1390	1300	1350	
Isolator	-	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	
Weld controller	-	Serratron 1A																



Prospot Limited – Unit C Riverside Industrial Estate
Atherstone Street – Fazeley – Tamworth – Staffordshire – B78 3RW
Telephone – 01827 254 829 Fax – 01827 254 832
Email – sales@prospot.co.uk Web – www.prospot.co.uk