

## Angled Offset Electrodes BS 807 5 Degree Inc Tapers

Material CuCrZr

Prospot No	Description	Electrode Dia	Taper Dia	Hole Dia	Taper Length	O/A Length	Spot Dia
PST13-45AO	1/2" Angled Offset Electrode	12.7	12.7	8	16	45	5
PST13-65AO	1/2" Angled Offset Electrode	12.7	12.7	8	16	65	5
PST16-55AO	5/8" Angled Offset Electrode	16	16	9	20	55	6
PST16-75AO	5/8" Angled Offset Electrode	16	16	9	20	75	6
PST19-75AO	3/4" Angled Offset Electrode	19	19	10	25	75	6



## Single Crank Offset Electrodes BS 807 5 Degree Inc Tapers

Material CuCrZr

Prospot No	Description	Electrode Dia	Taper Dia	Hole Dia	Taper Length	O/A Length	Spot Dia	Offset
500SCO	1/2" Single Crank Offset	12.7	12.7	8	20	60	5	19
625SCO	5/8" Single Crank Offset	16	16	9	28	88	5	38
750SCO	3/4" Single Crank Offset	19	19	9.5	38	100	6	25
750SCOL	3/4" Single Crank Offset	19	19	9.5	38	100	6	44



## Double Bend Offset Electrodes BS 807 5 Degree Inc Tapers

Material CuCrZr

Prospot No	Description	Electrode Dia	Taper Dia	Hole Dia	Taper Dia	O/A Length	Spot Dia	Offset
500DBO	1/2" Double Bend Offset	12.7	12.7	8	20	75	5	25
625DBO	5/8" Double Bend Offset	16	16	9	28	92	5	32
625DBOL	5/8" Double Bend Offset	16	16	9	28	92	5	38
750DBO	3/4" Double Bend Offset	19	19	9.5	38	108	6	32



## Swivel Electrodes BS 807 5 Degree Inc Tapers

Material CuCrZr

Prospot No	Description	Electrode Dia	Taper Dia	Hole Dia	Taper Length	O/A Length
SE1SWIVEL	1/2" Non Direct Cooled Swivel	30	12.7	8	13	50
SE1-22	1/2" Non Direct Cooled Swivel	22	12.7	8	13	50
SE2SWIVEL	5/8" Non Direct Cooled Swivel	30	16	9	20	60
SE2-22	5/8" Non Direct Cooled Swivel	22	16	9	20	60
SE3SWIVEL	3/4" Non Direct Cooled Swivel	30	19	9	22	60
SE1-DC	1/2" Direct Cooled Swivel	30	12.7	8	13	50
SE1-DC22	1/2" Direct Cooled Swivel	22	12.7	8	13	50
SE2-DC	5/8" Direct Cooled Swivel	30	16	9	20	60
SE2-DC22	5/8" Direct Cooled Swivel	22	16	9	20	6
SE3-DC	3/4" Direct Cooled Swivel	32	19	9	23	57

