




**WS 708**

- Half period welding time
- Single or multi spot
- Mains voltage automatic compensation
- 2 programs retrievable from the handle switch selector (external mode)
- 8 programs to be activated and used from the control keyboard
- Error messages
- Weld/no weld switch
- 24V DC solenoid valve
- 50/60 Hz frequency
- 24V AC mains supply for the control



**WS 708**



**Technical Specifications**

		<b>X-Gun 18</b>	<b>X-Gun 28</b>	<b>C-Gun 28</b>
Single phase input 50/60 Hz	V	400	400	400
Rated power at 50%	kVA	18	28	28
Max. welding power	kVA	58	88	98
Installed power	kVA	15	55	25
Delayed fuse	A	32	40	40
Open circuit voltage	V	4.8	5.8	5.8
Short circuit current	kA	15	19	21
Max. welding current	kA	12	15.2	16.8
Work stroke	mm	50	50	50 + 20
Electrode force max ( 6 bar )	daN	230	230	300
Water consumption a 200 kPa ( 3 bar )	l/min	4	4	4
Depth	mm	650	650	800
Width	mm	250	250	250
Height	mm	425	425	425
Weight	kg	47	53	58



Prospot Limited – Unit C Riverside Industrial Estate  
Atherstone Street – Fazeley – Tamworth – Staffordshire – B78 3RW  
Telephone – 01827 254 829 Fax – 01827 254 832  
Email – sales@prospot.co.uk Web – www.prospot.co.uk